



AWARD OF COLLECTOR CERTIFICATION

The solar collector listed below has been evaluated by the Solar Rating and Certification Corporation (SRCC) in accordance with SRCC Document OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC as specified in SRCC Standard 100-94, Test Methods and Minimum Standards for Certifying Solar Collectors. Certification and thermal performance ratings are based on the successful durability and performance testing of a sample unit where said tests have been conducted by an independent laboratory accredited by the SRCC.

Collector Certification Number: 100-2008006A

Certification Date: 26-APR-11

Type: Tubular

Expiration Date: 09-OCT-22

Test Laboratory: ITW

Report Number: 09COL814S

Report Date: 09-OCT-10

Brand: Soflower

Certified Model: SF-B155818

Model Tested: 2008006A

Supplier:

1st Sunflower Renewable Energy Co., Ltd

No.1, Hongxi Road, Niutang Industrial District

Changzhou, Jiangsu 213163 China

(86) 519-83051691

Description: Aluminum or stainless steel frame. Borosilicate cover. Aluminum absorber with Selective coating. Fiber, vacuum side insulation and fiber, vacuum back insulation. Water was the fluid for performance tests. Gross Area: 2.32 m^2 (25 ft²). Aperture Area: 1.42 m^2 (15.3 ft²).

		TUBUL	AR COLLE	CTOR THE	RM	AL PERFOR	MANCE RA	ATING		
Г	Megajoules Per Panel Per Day					Thousands of BTU Per Panel Per Day				
	CATEGORY (Ti-Ta)	CLEAR DAY	MILDLY CLOUDY	CLOUDY DAY		CATEGORY (Ti-Ta)	CLEAR DAY	MILDLY CLOUDY	CLOUDY DAY	
A	(-5 °C)	21.8	16.5	11.2	A	(-9 °F)	20.6	15.6	10.6	
В	(5 °C)	20.7	15.4	10.1	В	(9 °F)	19.6	14.6	9.6	
C	(20 °C)	19.0	13.7	8.4	С	(36 °F)	18.0	13.0	8.0	
D	(50 °C)	15.6	10.5	5.3	D	(90 °F)	14.8	10.0	5.1	
E	(80 °C)	12.2	7.0	2.5	E	(144 °F)	11.5	6.7	2.3	

A- Pool Heating (Warm Climate) B- Pool Heating (Cool Climate) C- Water Heating (Warm Climate) D- Water Heating (Cool Climate) E- Air Conditioning

	Efficiency Equatio	n [NOTE: Based on gross area and (P)=Ti-Ta	1
--	--------------------	--	---

YINTERCEPT

SLOPE

SI UNITS:

 η = 0.363 -1.15130 (P)/I

-0.00306 (P)²/I

0.365

-1.36 W/m².°C

I P UNITS:

η= 0.363

-0.20280 (P)/I

-0.00030 (P)²/I

0.365

-0.20 Btu/hr.ft².°F

Incident Angle Modifier [(S)=1/cosθ - 1, 0°<θ<=60°]

 $K\alpha = 1$

0.71 (S)

 $-0.260 (S)^2$

 $K\alpha = 1$

0.21 (S)

Linear Fit (S)2

REMARKS:

This award of certification is subject to all terms and conditions of the program Agreement and the documents incorporated therein by reference. It must be renewed annually. Any change in collector design, materials, specifications, parts, or construction must be reported to SRCC for evaluation of continued certification.

SRCC SRCC OG-100 CERTIFIED

Technical Director

April 26, 2011